

MARINE

MAINTENANCE

ALPHA PAINT REMOVER

PAINT AND VARNISH REMOVER

DESCRIPTION

ALPHA PAINT REMOVER is a fast-acting solvent based remover of all types of paints, revealing the original surface. This product rapidly penetrates the paint film, causing the film to wrinkle, bubble, and blister, resulting in its release from the substrate.

APPLICATION

ALPHA PAINT REMOVER is used degrading the paint film of metallic surfaces.

USE AND DOSING

Important Information and Precautions: Always make sure that there is sufficient ventilation to prevent the accumulation of gases and wear a breathing filter for acids. It is highly recommended to test **ALPHA PAINT REMOVER** in a small area of the surface, in order to conform suitability and desired results before the beginning of overall application.

Apply **ALPHA PAINT REMOVER** by brush or spraying and leave it for 15 to 30 minutes to penetrate, before rinsing it with water.

PRODUCT PROPERTIES

<u>General Instructions:</u> Avoid spillage, splashing and mishandling. Precautionary measures for body protection are strongly recommended before and during use.

Appearance:	Liquid	рН:	N/A
Type:	Organic based	Pour Point:	< - 15°C

- ✓ Paint remover
- ✓ Effective against corrosion
- ✓ Non-toxic
- Biodegradable
- ✓ Safe & easy to use

PROBLEMS SOLVED

- ✓ Rust
- ✓ Scale deposits

APPLICATION AREAS

- Machinery parts
- ✓ Nuts
- ✓ Bolts

PRODUCT CODE: MC 075