



FT 500

FLOW IMPROVER, ASPHALTENE
AND FUEL OIL DEPOSITS DISPERSANT

DESCRIPTION

FT 500 comprises a mixture of special cleaning agents, asphaltene dispersants and strong solvents, and is suitable to use in any type of fuel, especially in heavy fuels with high viscosity. **FT 500** effectively acts as flow improver and fuel stabilizer, but also as a dispersant for any residues and deposits thus keeping the tanks and the entire fuel network clean.

APPLICATION & USE

Apply **FT 500**, to optimize the fluidity of heavy fuels, prevent the fuel from freezing during winter, disperse the existing sludge and deposits in the fuel and prevent new deposition.

FT 500 breaks down water-fuel emulsions, prevents stratification of fuel in the tank, prevents corrosion and significantly helps better fuel injection resulting in improved combustion.

Add **FT 500** into the fuel tank before refueling at a dose of 1 liter of **FT 500** per 3000 up to 5000 liters of fuel. The dosage depends on the type of fuel and the size of the problem.

PACKAGING

FT 500 is available in 25 ltr pails and 208 ltr drums.

- ✓ Improves the fluidity of heavy fuels & breaks down existing asphaltene
- ✓ Efficient disperser of residues & fuel deposits, keeps the network clean
- ✓ Prevents filters clogging and improves fuel injection and therefore combustion
- ✓ Acts as fuel stabilizes and prevents stratification
- ✓ Protects tanks and fuel grid from corrosion
- ✓ Concentrated product
- ✓ Added in very small dosage

PRODUCT CODE: FA112-21